



NOTES:

1. MATERIAL: COPPER ALLOY.
STRIP THICKNESS: 0.25 mm.
2. CONTINUOUS STRIP ON REELS.
3. APPLICATION DATA:
WIRE: 0.2~0.5 mm²
INSULATION: Ø 2.4 mm MAX.

DIST	LOC	PLTR	REVISION/RECORD	DATE	DWG	APPD
0			FH10-0004-02 NEW REL	Nov.8.02	AM	SFS
A			FH10-0012-03	27/10/03	BW	SFS
B			FH10-0028-03	19/11/03	BW	SFS
B1			REVISION PER ECR-19-013140	22/12/20	SS	EW

TOLERANCES UNLESS OTHER SPECIFIED: 0 P.L.C ± 0.20 1 P.L.C ± 0.15 2 P.L.C ± 0.15 3 P.L.C ± 0.15 4 P.L.C ± 0.15 ANGLE ± 1°		DR ALAN MO CHK BORIS WONG APP'D S.F. SHUM PRODUCT SPEC 108-58501		DATE OCT.25.02 DATE NOV.04.02 DATE NOV.06.02		MATERIAL SHE NOTE FINISH "X" FINISH P/N	
APPLICATION SPEC 114-58500 RESTRICTED TO 1:1 SCALE A3 SIZE A3		NAME SIZE (2.8) FASTON RECPPT. TE Connectivity		DATE OCT.25.02 DATE NOV.04.02 DATE NOV.06.02		REV 1 REV 1 REV B1	

