#### UL Product **iQ**™



E522540

# ZODZ2.E522540 - Positioning Devices - Component

## Positioning Devices - Component

**Tyco Electronics France SAS** 

3 rue Jean Perrin CHASSIEU, 69680 France

#### Positioning Devices Investigated to ANSI/UL 1565

Catalog No.	Maximum Use Temp,°C	
PC/ABS Wiring Ducts (gray color)		
WD-1-DH-GR2530	90	
WD-1-DH-GR2540	90	
WD-1-DH-GR2560	90	
WD-1-DH-GR4040	90	
WD-1-DH-GR4060	90	
WD-1-DH-GR4080	90	
WD-1-DH-GR6040	90	
WD-1-DH-GR6060	90	
WD-1-DH-GR6080	90	
WD-1-DH-GR8060	90	
WD-1-DH-GR8080	90	
PVC Wiring Ducts (all colors)		
WD-1-DP-GR1001	50	
WD-1-DP-GR1006	50	
WD-1-DP-GR1008	50	
WD-1-DP-GR1201	50	
WD-1-DP-GR1206	50	
WD-1-DP-GR1208	50	
WD-1-DP-GR2510	50	
WD-1-DP-GR2530	50	

WD-1-DP-GR2540	50
WD-1-DP-GR2560	50
WD-1-DP-GR2580	50
WD-1-DP-GR4010	50
WD-1-DP-GR4040	50
WD-1-DP-GR4060	50
WD-1-DP-GR4080	50
WD-1-DP-GR6010	50
WD-1-DP-GR6040	50
WD-1-DP-GR6060	50
WD-1-DP-GR6080	50
WD-1-DP-GR8010	50
WD-1-DP-GR8040	50
WD-1-DP-GR8060	50
WD-1-DP-GR8080	50

Marking: Company name, catalog or model number and the Recognized Component Mark, . . . If published with the product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2021-06-01

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

#### UL Product iQ™



# ZODZ8.E522540 - Positioning Devices Certified for Canada - Component

### Positioning Devices Certified for Canada - Component

**Tyco Electronics France SAS** 

E522540

3 rue Jean Perrin CHASSIEU, 69680 France

#### Positioning Devices Investigated to CSA-C22.2 No. 18.5

Catalog No.	Maximum Use Temp,°C
PC/ABS Wiring Ducts (gray color)	
WD-1-DH-GR2530	90
WD-1-DH-GR2540	90
WD-1-DH-GR2560	90
WD-1-DH-GR4040	90
WD-1-DH-GR4060	90
WD-1-DH-GR4080	90
WD-1-DH-GR6040	90
WD-1-DH-GR6060	90
WD-1-DH-GR6080	90
WD-1-DH-GR8060	90
WD-1-DH-GR8080	90
PVC Wiring Ducts (all colors)	
WD-1-DP-GR1001	50
WD-1-DP-GR1006	50
WD-1-DP-GR1008	50
WD-1-DP-GR1201	50
WD-1-DP-GR1206	50
WD-1-DP-GR1208	50

50

WD-1-DP-GR2510

WD-1-DP-GR2530	50
WD-1-DP-GR2540	50
WD-1-DP-GR2560	50
WD-1-DP-GR2580	50
WD-1-DP-GR4010	50
WD-1-DP-GR4040	50
WD-1-DP-GR4060	50
WD-1-DP-GR4080	50
WD-1-DP-GR6010	50
WD-1-DP-GR6040	50
WD-1-DP-GR6060	50
WD-1-DP-GR6080	50
WD-1-DP-GR8010	50
WD-1-DP-GR8040	50
WD-1-DP-GR8060	50
WD-1-DP-GR8080	50

Marking: Company name, catalog or model number and the Recognized Component Mark for Canada, and, if published with the

product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2021-06-01

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"