

CERTIFICATE OF COMPLIANCE

Certificate Number 20140514-E28476
Report Reference E28476-20061021
Issue Date 2014-MAY-14

Issued to: TYCO ELECTRONICS CORP
2901 FULLING MILL RD
MIDDLETOWN PA 17057-3170

**This is to certify that
representative samples of**


Component – Connectors For Use In Data, Signal Control
and Power Applications
See addendum page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1977 - Component Connectors for Use in Data, Signal,
Control and Power Applications


Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Recognized Component Mark should be considered as being covered by UL's Recognition and Follow-Up Service.

The UL Recognized Component Mark generally consists of the manufacturer's identification and catalog number, model number or other product designation as specified under "Marking" for the particular Recognition as published in the appropriate UL Directory. As a supplementary means of identifying products that have been produced under UL's Component Recognition Program, UL's Recognized Component Mark: , may be used in conjunction with the required Recognized Marks. The Recognized Component Mark is required when specified in the UL Directory preceding the recognitions or under "Markings" for the individual recognitions.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Recognized Component Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus




CERTIFICATE OF COMPLIANCE

Certificate Number 20140514-E28476
Report Reference E28476-20061021
Issue Date 2014-MAY-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Component Connector, Series Model(s) DTM, followed by 13 or 15, followed by 2, 3, 4, 6, 08, or 12, followed by P or S. May be followed by suffixes denoting minor variations.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



File E28476
Service Request: 1181364

October 21, 2006

REPORT

on

COMPONENT - CONNECTORS FOR USE IN DATA, SIGNAL, CONTROL AND POWER
APPLICATIONS

TYCO ELECTRONICS CORP
MIDDLETOWN, PA

Copyright © 2006 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report either in its entirety or the portion of this Report consisting of the Cover Page up to (but not including) the Construction Details Descriptive pages.

DESCRIPTION

PRODUCT COVERED:

USR Component Connector, Series Model(s) DTM, followed by 13 or 15, followed by 2, 3, 4, 6, 08, or 12, followed by P or S. May be followed by suffixes denoting minor variations.

GENERAL:

These devices are multi-pole connectors intended for factory assembly soldered to PWB where the acceptability of combinations is determined by Underwriters Laboratories Inc. The devices are identified as follows:

* USR indicates investigation to United States Standards, UL 1977.

RATINGS:

Series	Type Contact	Amperage	Voltage, Vac
DTM	PWB solder tails	7.5	250

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in or with complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

1. These devices have not been tested for interrupting the flow of current by connecting or disconnecting the mating connector. These devices should be used only where they will not interrupt the flow of current.
2. The current rating was determined based upon similarity to same construction, except for solder connectors.

3. These devices may be used at potentials not exceeding 250 V based on Dielectric Voltage-Withstand testing conducted at 1500 V ac.

4. The operating temperature of these devices should not exceed the temperature ratings of the insulating materials, a maximum temperature of 65°C **when employing plastic** TE Proprietary Information

5. Mold Stress Relief testing was conducted at a temperature of 75°C **when employing plastic** TE Proprietary Information

6. These devices employ insulating materials with properties as tabulated below at the minimum thickness employed in the connector housing, the suitability of the insulating materials based on the documented values shall be determined in the end-use application. Please note the values specified in the table when multiple materials are indicated represent the minimum values for the group of materials.

Cat. No.	Insulating Material (#)	Measured Minimum Thickness	Flame Class	HWI	HAI	RTI Elec	Max Operating Temp, °C
DTM housing	A	0.5 mm	(+)	(++)	(++)	120	65
DTM Housing	B	0.5 mm	V-0	0	0	140	125

Note:

(#) - Code for Insulating Body Material.

(+): Thickness is less than the minimum Recognized material thickness, as such no assigned Flame class. UL 746C (12mm) (20mm) Flammability test conducted.

(++): These PLCs are based on the minimum Recognized material thickness.

A. TE Proprietary Information

1. Dielectric strength (kV/mm): -
2. CTI: -

B. TE Proprietary Information

1. Dielectric strength (kV/mm): 23
2. CTI: 2

Nomenclature - The Series are designated as follows:

DTM Series Example

Example: $\frac{\text{DTM}}{\text{I}} \frac{13}{\text{II}} - \frac{3}{\text{III}} \frac{\text{S}}{\text{IV}} \frac{\text{*****}}{\text{V}}$

I: - Series Prefix
DTM only

II: - Type Enclosure

13 - Receptacle right angle and outlets (Female)
15 - Receptacle (Female)+ outlet

III: - Number of Contacts, maybe 2, 3, 4, 6, 08, or 12.

IV: - Contact Type
P - Pin

V: - Polarizing position (if applicable, 08 & 12 Only)
And /or minor order variations not affecting construction as described herein.