

Certificate of Compliance

Certificate Number:

UL-US-2428895-0

Report Reference:

E28476-20090715

Issue Date:

2024-07-26

Issued to:

**TYCO Electronics Corp
2901 Fulling Mill Rd Middletown, PA 17057
United States**

This certificate confirms that representative samples of:

ECBT2 - Connectors for Use in Data, Signal, Control and Power Applications - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1977, Edition 4, Issue Date 2022-12-07

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2428895-0
Report reference E28476-20090715
Date 2024-07-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
20090715, DRC1	Connectors
DRC10-24PX-XXXX	Connectors
DRC10-40P-XXXX	Connectors
DRC12-24PXZ-XXXX	Connectors
DRC12-40PXZ-XXXX	Connectors
DRC12-70PXZ-XXXX	Connectors
DRC13-24PX-XXXX	Connectors
DRC13-40PX-XXXX	Connectors
DRC14-24PXZ-XXXX	Connectors
DRC14-40PXZ-XXXX	Connectors
DRC14-70PXZ-XXXX	Connectors
DRC16-24SXZ-XXXX	Connectors
DRC16-40SZ-XXXX	Connectors
DRC16-70SXZ-XXXX	Connectors
20090715, DRC18	Connectors
DRC18-40SXZ-XXXX	Connectors
DRC20-50PX-XXXX	Connectors
DRC20-60PX-XXXX	Connectors
DRC20-75PXX-XXXX	Connectors
DRC22-40PX-XXXX	Connectors
DRC22-50PX-XXXX	Connectors
DRC23-24PX-XXXX	Connectors
DRC23-40PX-XXXX	Connectors
DRC23-64PX-XXXX	Connectors
DRC23-80P	Connectors
20090715, DRC26	Connectors
DRC26-24SX-XXXX	Connectors
DRC26-38SX-XXXX	Connectors
DRC26-40SX-XXXX	Connectors
DRC26-50SX-XXXX	Connectors
DRC26-60SX-XXXX	Connectors



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



Certificate of Compliance

Certificate Number:

UL-US-L28476-1125-
51709002-6

Report Reference:

E28476-20090715

Issue Date:

2024-07-26

Issued to:

TYCO Electronics Corp
2901 Fulling Mill Rd Middletown, PA 17057
United States

This certificate confirms that representative samples of:

ECBT2 - Connectors for Use in Data, Signal, Control and Power Applications - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1977, Edition 4, Issue Date 2022-12-07

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L28476-1125-51709002-6
Report reference E28476-20090715
Date 2024-07-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
20090715, DRC1	Connectors
DRC10-24PX-XXXX	Connectors
DRC10-40P-XXXX	Connectors
DRC12-24PXZ-XXXX	Connectors
DRC12-40PXZ-XXXX	Connectors
DRC12-70PXZ-XXXX	Connectors
DRC13-24PX-XXXX	Connectors
DRC13-40PX-XXXX	Connectors
DRC14-24PXZ-XXXX	Connectors
DRC14-40PXZ-XXXX	Connectors
DRC14-70PXZ-XXXX	Connectors
DRC16-24SXZ-XXXX	Connectors
DRC16-40SZ-XXXX	Connectors
DRC16-70SXZ-XXXX	Connectors
20090715, DRC18	Connectors
DRC18-40SXZ-XXXX	Connectors
DRC20-50PX-XXXX	Connectors
DRC20-60PX-XXXX	Connectors
DRC20-75PXX-XXXX	Connectors
DRC22-40PX-XXXX	Connectors
DRC22-50PX-XXXX	Connectors
DRC23-24PX-XXXX	Connectors
DRC23-40PX-XXXX	Connectors
DRC23-64PX-XXXX	Connectors
DRC23-80P	Connectors
20090715, DRC26	Connectors
DRC26-24SX-XXXX	Connectors
DRC26-38SX-XXXX	Connectors
DRC26-40SX-XXXX	Connectors
DRC26-50SX-XXXX	Connectors
DRC26-60SX-XXXX	Connectors



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



File E28476
Service Request: 1181364

July 15, 2009

REPORT

on

COMPONENT - Connectors for Use in Data, Signal, Control and Power Applications

TYCO ELECTRONICS CORP
MIDDLETOWN, PA

Copyright © 2009 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report provided it is in its entirety.

Underwriters Laboratories Inc. authorizes the above named company to reproduce the latest pages of that portion of this Report consisting of this Cover Page through Page 5.

DESCRIPTION

PRODUCT COVERED:

USR Component Connectors, Series DRC1, DRC18, DRC26.

* Cat Nos. **DRC10-24PX-XXXX, DRC10-40P-XXXX, DRC12-24PXZ-XXXX, DRC12-40PXZ-XXXX, DRC12-70PXZ-XXXX, DRC13-24PX-XXXX, DRC13-40PX-XXXX, DRC14-24PXZ-XXXX, DRC14-40PXZ-XXXX, DRC14-70PXZ-XXXX, DRC16-24SXZ-XXXX, DRC16-40SZ-XXXX, DRC16-70SXZ-XXXX, DRC18-40SXZ-XXXX, DRC20-50PX-XXXX, DRC20-60PX-XXXX, DRC20-75PXX-XXXX, DRC22-40PX-XXXX, DRC22-50PX-XXXX, DRC23-24PX-XXXX**
***DRC23-40PX-XXXX, DRC23-64PX-XXXX, DRC23-80P, DRC26-24SX-XXXX, DRC26-38SX-XXXX, DRC26-40SX-XXXX, DRC26-50SX-XXXX, DRC26-60SX-XXXX.**

Refer to Nomenclature portion of report for Cat. Nos.

GENERAL:

These devices are multi-pole connectors intended for factory assembly on stranded copper conductors where the acceptability of combinations is determined by Underwriters Laboratories Inc. The devices are identified as follows:

* USR indicates investigation to United States Standards **referenced in the Test Records.**

RATING:

No current or voltage

Flammability -

Disconnecting Use - see Sec Gen for required marking

and Report

NOMENCLATURE:

*	DRC	1	4	-	40	P	X	Z	-	XXXX
	I	II	III		IV	V	VI	VII		VIII

I. Designates Deutsch Rectangular Connector Bulk Packaged without Contacts or Accessories.

II. Indicates Contact Type

1 = Accepts Size 16 Terminals

2 = Accepts Size 20 Terminals

III. Indicates Connector Style

* 0 = **180° Receptacle PCB Termination**

2 = Receptacle - Flange Mount

* 3 = 90° Receptacle PCB Termination

4 = Receptacle - Inline

*

6 = Plug

8 = Keyed Plug 40 Pin Size 16 Only

IV. Indicates Shell Size and Insert Layout

24 = 24 pole

38 = 38 poles

40 = 40 pole

50 = 50 poles

60 = 60 poles

70 = 70 pole

75 = 75 poles

76 = 76 poles

80 = 80 poles

V. Indicates Contact Style

* S = Socket (**Plug**)

* P = Pin (**Receptacle**)

* VI. Keying Position

Blank = **No Key**

A, B, C, D or 01 through 10

*

VII. Wire Seals

* Blank = **Normal** Wire Insulation Seal

* T = Thin Wall Wire Insulation Seal

* E = Extra Thin Wire Insulation Wall Seal

VIII. Special Modifications

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in or with complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - The following are among the considerations to be made when evaluating the device in the end-use product.

Interruption of Current

1. These devices are not suitable for interrupting the flow of current by connecting or disconnecting the mating connector.

Current-Carrying Capability and Current Ratings

2. These devices have not been subjected to the Temperature test and as a result do not have an assigned current rating. The device's current carrying capability is to be reviewed in the end-use by measuring temperatures on the connector housing and/or terminals when current is flowing through the connector under conditions of normal use.

Insulating Materials

*

*3. These devices employ insulating materials with properties as tabulated below at the minimum thickness employed in the connector housing, the suitability of the insulating materials based on the documented values shall be determined in the end-use application. Please note the values specified in the table when multiple materials are indicated represent the minimum values for the group of materials.

and Report

Part	TE RM # Insulating Material #	Manufacture	Min Thicknes s (mm)	Flam e Clas s	HWI	HA I	RTI Elec	Max Operating Temp °C
Plug/Rcp t Housing Size 16	(A)		1.78	V-0	4	1	130	125
	(E)		1.78	V-0	-	-	130	125
Plug/Rcp t Housing Size 20	(A)		1.40	V-0	4	1	130	125
	(D)		1.40	V-0	0	0	140	125
	(E)		1.40	V-0	-	-	130	125
Header Housing Size 16	(A)		1.27	V-0	4	1	130	125
	(E)		1.27	V-0	-	-	130	125
Header Housing Size 20	(A)		1.02	V-0	4	1	130	125
	(D)		1.02	V-0	0	0	140	125
	(E)		1.02	V-0	-	-	130	125
Retainer Size 16	(B)		1.14	V-0	2	4	170	125
	(C)		1.14	HB	3	0	- -	65
	(D)		1.14	V-0	0	0	140	125
Retainer Size 20	(B)		0.98	V-0	2	4	170	125

Note:

(#) - Code for Insulating Body Material.

- A. TE RM No. [REDACTED]
Color: Black
1. Dielectric strength (kV/mm): 17
2. CTI: 4
- B. TE RM No. [REDACTED]
Color: Black
1. Dielectric strength (kV/mm): 32
2. CTI: 4
- C. TE RM No. [REDACTED]
1. Dielectric strength (kV/mm): --
2. CTI: --
- D. TE RM No. [REDACTED]
Color: Black
1. Dielectric strength (kV/mm): 23
2. CTI: 2
- *E. TE RM No. [REDACTED]
Color: Black
1. Dielectric Strength (kV/mm): - -
2. CTI: 4

4. The Maximum Operating Temperature of these devices should not exceed the temperature ratings of the insulating materials. These materials may be used interchangeably at a maximum temperature of 65°C **for the Size 16 Connectors and 125°C for the Size 20 Connectors.**

5. These devices have been evaluated for a 20 mm Flame Test per applicant request. The suitability of the insulating materials shall be determined in the end-use application. Devices employing housings molded from Stanyl TE250F6 have not been subjected to the 20 mm Flame Test.

Terminations

7. The following crimp contacts have been evaluated for the wire sizes as tabulated below:

Stamped and Formed Type -

Pin/Contact	Contact Size	Wire Size, AWG	Force, lbf
1060-12-0166 / 1062-12-0166	12	12, 14	20
1060-12-0222 / 1062-12-0222	12	10	20
1060-14-0122 / 1062-14-0122	16	14 - 18	20
1060-16-0122 / 1062-16-0122	16	14 - 18	20
1060-16-0622 / 1062-16-0622	16	16, 18	20
1060-16-0622 / 1062-16-0622	16	20	8
1060-16-1222 / 1062-16-1222	16	12, 16	20
1062-16-14xx	16	12 - 16	20
1060-20-0122 / 1062-20-0122	20	16, 18	20
1060-20-0122 / 1062-20-0122	20	20	8
1060-20-01xx / 1062-20-01xx	20	22	8
	20		
1060-20-0222 / 1062-20-0222	20	16, 18	20
1060-20-0222 / 1062-20-0222	20	20	8
1060-20-02xx / 1062-20-02xx	20	22	8
1060-20-0144	20	16	20
	20	18	20
	20	20	8
1062-20-03xx	20	16 18	20
1062-20-03xx	20	20	8
1062-20-03xx	20	22	8

Solid Type -

Pin/Contact	Contact Size	Wire Size, AWG	Force, lbf
0460-202-20141	20	20	8
0462-201-20141	20	20	8
0460-202-20xxx / 0462 201 20xxx	16	22	8
0460-215-16141 / 0462-209-16141	16	14	20
0460-204-12141 / 0462-203-12141	12	12, 14	20
0460-202-16141 / 0462-201-16141	16	16, 18	20
0460-202-16141 / 0462-201-16141	16	20	8