Certificate Number Report Reference Date UL-CA-2133757-0 E507163-20210824 27-Aug-2021

Issued to: TYCO ELECTRONICS (SHANGHAI) CO LTD Sections F, G and H, Level 1, Building 15 No. 999, Yinglun Road, China (Shanghai) Pilot Free Trade Zone SHANGHAI China 200131

This is to certify that representative samples of

DUXR7 - Communications-, Audio/Video-, Data- and Other Signaling-circuit Accessories Certified for Canada See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

 
 Standard(s) for Safety:
 CAN/CSA-C22.2 NO. 182.4-M90, 1st Ed., Issue Date: 1990-05-01, Reaffirmed 2020, CSA C22.2 NO. 233-17, 3rd Ed., Issue Date: 2017-05-01

Additional Information: See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

Certificate Number Report Reference Date UL-CA-2133757-0 E507163-20210824 27-Aug-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
TAXSBXWYOMN-XXX, T representing TE Brand. A in models TAXSBXWYOMN-XXX representing M12 series. C in models TCXSBXWYOMN-XXX representing M12 TO RJ45. 1st X representing X-Code. S representing Application Type, it can be 3, which means Shielding Industrial Ethernet Cate 6A. B representing Poles No., it can be 8, which means 8 Poles. 2nd X representing Interface Type, it can be 7 or 8 or B, 7 representing male straight to male straight, 8	Category Description Ethernet Cable
representing Male straight to male angled, B representing male angled to male angled. W representing Wire Gauge, it can be 2, which means 26AWG. Y representing Cable Jacket, it can be 1 or 5 or A, 1 representing PVC cable, 5 representing PUR cable, A representing TPE cable. O representing Cable Color, it can be 1 or 2, 1 representing Green (for PVC&PUR), 2 representing Teal	
(only for TPE). M representing Over-Molding, it can be 0 or 1, 0 representing black TPU Over-molding for TPE/PUR cable, 1 representing black PVC Over-molding for PVC cable. N representing Other, it can be 2, which means Zinc alloy screw nut with Nickel plated. -XXX representing cable Length, it can be any 3-diagit of	
number. TCXSBXWYOMN-XXX, T representing TE Brand. A in models TAXSBXWYOMN-XXX representing M12 series. C in models TCXSBXWYOMN-XXX representing M12 TO RJ45. 1st X representing X-Code. S representing Application Type, it can be 3, which means Shielding Industrial Ethernet Cate 6A. B representing Poles No., it can be 8, which means 8 Poles.	Ethernet Cable

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <a href="http://ul.com/aboutul/locations/">http://ul.com/aboutul/locations/</a>

Certificate Number Report Reference Date

UL-CA-2133757-0 E507163-20210824 27-Aug-2021

2nd X representing Interface Type, it can be 7 or 8 or B, 7 representing male straight to male straight, 8 representing Male straight to male angled, B representing male angled to male angled. W representing Wire Gauge, it can be 2, which means 26AWG. Y representing Cable Jacket, it can be 1 or 5 or A, 1 representing PVC cable, 5 representing PUR cable, A representing TPE cable. O representing Cable Color, it can be 1 or 2, 1 representing Green (for PVC&PUR), 2 representing Teal (only for TPE). M representing Over-Molding, it can be 0 or 1, 0 representing black TPU Over-molding for TPE/PUR cable, 1 representing black PVC Over-molding for PVC cable. N representing Other, it can be 2, which means Zinc alloy screw nut with Nickel plated. -XXX representing cable Length, it can be any 3-diagit of number.

Bampleg



UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

Certificate Number Report Reference Date UL-US-2140281-0 E507163-20210824 27-Aug-2021

Issued to: TYCO ELECTRONICS (SHANGHAI) CO LTD Sections F, G and H, Level 1, Building 15 No. 999, Yinglun Road, China (Shanghai) Pilot Free Trade Zone SHANGHAI China 200131

This is to certify that representative samples of

thatDUXR - Communications-, Audio/Video-, Data- and Otheres ofSignaling-circuit Accessories

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety:	UL 1863, 4th Ed, Issue Date: 2004-05-14, Revision Date:
	2019-10-14

Additional Information: See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

ULL LLC

Bruce Mahrenholz, Director North American Certification Program



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at <a href="http://ul.com/aboutul/locations/">http://ul.com/aboutul/locations/</a>

Certificate Number Report Reference Date UL-US-2140281-0 E507163-20210824 27-Aug-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
Model         TAXSBXWYOMN-XXX, T representing TE Brand.         A in models TAXSBXWYOMN-XXX representing M12 series.         C in models TCXSBXWYOMN-XXX representing M12 TO RJ45.         1st X representing X-Code.         S representing Application Type, it can be 3, which means Shielding Industrial Ethernet Cate 6A.         B representing Poles No., it can be 8, which means 8 Poles.         2nd X representing Interface Type, it can be 7 or 8 or B, 7 representing male straight to male straight, 8	Category Description Ethernet Cable
representing Male straight to male angled, B representing male angled to male angled. W representing Wire Gauge, it can be 2, which means	
26ÅWG. Y representing Cable Jacket, it can be 1 or 5 or A, 1 representing PVC cable, 5 representing PUR cable, A representing TPE cable. O representing Cable Color, it can be 1 or 2, 1	
representing Green (for PVC&PUR), 2 representing Teal (only for TPE). M representing Over-Molding, it can be 0 or 1, 0 representing black TPU Over-molding for TPE/PUR cable, 1 representing black PVC Over-molding for PVC	
cable. N representing Other, it can be 2, which means Zinc alloy screw nut with Nickel plated. -XXX representing cable Length, it can be any 3-diagit of number.	
TCXSBXWYOMN-XXX, T representing TE Brand. A in models TAXSBXWYOMN-XXX representing M12 series.	Ethernet Cable
C in models TCXSBXWYOMN-XXX representing M12 TO RJ45.	
1st X representing X-Code. S representing Application Type, it can be 3, which means Shielding Industrial Ethernet Cate 6A.	
B representing Poles No., it can be 8, which means 8 Poles.	

Bamely

Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <a href="http://ul.com/aboutul/locations/">http://ul.com/aboutul/locations/</a>

Certificate Number Report Reference Date

UL-US-2140281-0 E507163-20210824 27-Aug-2021

2nd X representing Interface Type, it can be 7 or 8 or B, 7 representing male straight to male straight, 8 representing Male straight to male angled, B representing male angled to male angled. W representing Wire Gauge, it can be 2, which means 26AWG. Y representing Cable Jacket, it can be 1 or 5 or A, 1 representing PVC cable, 5 representing PUR cable, A representing TPE cable. O representing Cable Color, it can be 1 or 2, 1 representing Green (for PVC&PUR), 2 representing Teal (only for TPE). M representing Over-Molding, it can be 0 or 1, 0 representing black TPU Over-molding for TPE/PUR cable, 1 representing black PVC Over-molding for PVC cable. N representing Other, it can be 2, which means Zinc alloy screw nut with Nickel plated. -XXX representing cable Length, it can be any 3-diagit of number.

Bampleg



UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/