

File E28476
Project 91ME31336

December 30, 1991

REPORT

On

COMPONENT - RECEPTACLES FOR ATTACHMENT PLUGS AND PLUGS

AMP Inc.
Harrisburg, PA

Copyright © 1991 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 2.

DESCRIPTION

PRODUCT COVERED:

Component Connectors - AMP FH Connector Series.

GENERAL:

These devices are multi-pole connectors employing contacts of the solder termination type and surface mount type for use with printed circuit boards.

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

1. These devices should be used only where they will not interrupt the current.
 2. These devices have not been tested for current-carrying capability.
 3. The suitability of the mounting means shall be determined in the end use.
 4. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.
- *
5. The electrical and mechanical contact between the connector and the printed wiring board is to be judged in the end-use equipment.
 6. The suitability of the insulating materials used in the molded bodies shall be judged in the end-use equipment.
 7. The operating temperature of these devices should not exceed the temperature ratings of the insulating materials. These materials may be used interchangeably at a maximum temperature of 130°C.