






7. CONTACT AREA LUBRICATED WITH BELLCORE  
APPROVED LUBRICANT. TECHNICAL REFERENCE:  
GR-1217-CORE, ISSUE 1, NOVEMBER 1995.



	$\varnothing 0.05$		X	Y
---	--------------------	---	---	---

 ALL PLATED  
THRU HOLES

2274073-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG AJITH PAI 17AUG2017 CHK R.A. PATTERSON 17AUG2017 APP'D R. PATTERSON 18AUG2017		 TE Connectivity	
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 1 PLC ±. 2 PLC ±. 3 PLC ±. 4 PLC ±. ANGLES ±. FINISH		NAME HEADER ASSEMBLY, 3 PAIR, SELECTIVELY LOADED, 2.5mm TAIL, 25mm, HMZd	
MATERIAL 		PRODUCT SPEC APPLICATION SPEC WEIGHT -		SIZE A1	CAGE CODE -
		CUSTOMER DRAWING		DRAWING NO C=2274073	RESTRICTED TO -
				SCALE 8:1	SHEET 1 OF 1
				REV A	