

# SPECIFICATION CONTROL DRAWING

**55PC0832**

TITLE

THREE CONDUCTOR CABLE,  
UNSHIELDED, UNJACKETED, 600 VOLT

Date

10-6-98

Revision

C

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0812



### CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	DIAMETER ( in. )			WEIGHT ( lbs/1000 ft. )	
		LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC0832-24-*	24	.089	.094	.098	6.63	6.94
55PC0832-22-*	22	.102	.107	.111	9.49	9.83
55PC0832-20-*	20	.120	.125	.130	14.12	14.54
55PC0832-18-*	18	.141	.147	.152	21.11	21.75
55PC0832-16-*	16	.158	.164	.170	26.77	27.51
55PC0832-14-*	14	.192	.198	.204	41.06	42.09
55PC0832-12-*	12	.231	.238	.245	62.19	63.53
55PC0832-10-*	10	.277	.287	.296	96.49	98.72
55PC0832- 8-*	8	.404	.421	.439	173.	180.
55PC0832- 6-*	6	.501	.522	.542	273.	285.
55PC0832- 4-*	4	.646	.670	.695	444.	464.
55PC0832- 2-*	2	.793	.825	.857	689.	724.

### CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C  
 Maximum continous conductor temperature  
 VOLTAGE RATING: 600 volts (rms)  
 INSULATION FLAWS:  
 Impulse Dielectric Test, 8.0 kV (peak)

PART NUMBER:  
 The "\*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors.  
 Example: AWG 22, black, white and red component wires; 55PC0832-22-0/9/2

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-881.

**Raychem**

Raychem Corporation  
 300 Constitution Drive, Menlo Park, California 94025  
 1-800-2 Raychem FAX: 1-650-361-6297