

4

3

2

1

© - TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
F1		REVISED PER ECR-23-179060	08SEP2023	AK	JP

OBSOLETE

1 MATERIAL: CONNECTOR - NYLON UL94V-2 (RED).  
CONTACTS - 0.30[.012] THICK COPPER ALLOY BRIGHT TIN-LEAD .00203[.000080] MIN THICKNESS FOR 644540-2 THRU 2-644540-8.  
MATTE WHISKER MITIGATED TIN .00203[.000080] MIN THICKNESS OVER NICKEL UNDERPLATE FOR 3-644540-2 THRU 4-644540-5.

2 CONTACTS ACCEPT 22 AWG WIRE WITH 1.52[.060] MAX INSULATION DIAMETER.

3 CONTACTS MUST ACCEPT 0.64±0.03[.025±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.

4 IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.

5 DIMENSIONS IN BRACKETS ARE IN INCHES.

6 HOUSING FEATURES ARE: FEED THRU WITH LOCKING RAMP AND WITH POLARIZING TAB.

7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8 OBSOLETE PARTS

YES	38.10[1.500]	15	4-644540-5
YES	35.56[1.400]	14	4-644540-4
YES	33.02[1.300]	13	4-644540-3
YES	30.48[1.200]	12	4-644540-2
YES	27.94[1.100]	11	4-644540-1
YES	25.40[1.000]	10	4-644540-0
YES	22.86[.900]	9	3-644540-9
YES	20.32[.800]	8	3-644540-8
YES	17.78[.700]	7	3-644540-7
YES	15.24[.600]	6	3-644540-6
YES	12.70[.500]	5	3-644540-5
YES	10.16[.400]	4	3-644540-4
YES	7.62[.300]	3	3-644540-3
YES	5.08[.200]	2	3-644540-2

NO	38.10[1.500]	15	1-644540-5	SUPERSEDED BY 4-644540-5	7
NO	35.56[1.400]	14	1-644540-4	SUPERSEDED BY 4-644540-4	8
NO	33.02[1.300]	13	1-644540-3	SUPERSEDED BY 4-644540-3	7
NO	30.48[1.200]	12	1-644540-2	SUPERSEDED BY 4-644540-2	8
NO	27.94[1.100]	11	1-644540-1	SUPERSEDED BY 4-644540-1	8
NO	25.40[1.000]	10	1-644540-0	SUPERSEDED BY 4-644540-0	7
NO	22.86[.900]	9	-644540-9	SUPERSEDED BY 3-644540-9	8
NO	20.32[.800]	8	-644540-8	SUPERSEDED BY 3-644540-8	8
NO	17.78[.700]	7	-644540-7	SUPERSEDED BY 3-644540-7	8
NO	15.24[.600]	6	-644540-6	SUPERSEDED BY 3-644540-6	8
NO	12.70[.500]	5	-644540-5	SUPERSEDED BY 3-644540-5	8
NO	10.16[.400]	4	-644540-4	SUPERSEDED BY 3-644540-4	8
NO	7.62[.300]	3	-644540-3	SUPERSEDED BY 3-644540-3	8
NO	5.08[.200]	2	-644540-2	SUPERSEDED BY 3-644540-2	8

LEADFREE	DIM A	NO. OF CIRCUITS	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. CARPENTER 12JUN2003		
DIMENSIONS: mm [INCHES]		CHK D. BOSSI 12JUN2003		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. BOSSI 12JUN2003	NAME MTA 100 CONNECTOR ASSEMBLY, 22 AWG, STANDARD	
0 PLC ±		PRODUCT SPEC 108-1050	SIZE A2	
1 PLC ±		APPLICATION SPEC 114-1019	CAGE CODE 00779	DRAWING NO C=644540
2 PLC ±		MATERIAL 1	RESTRICTED TO -	
3 PLC ± 0.13 [.005]		FINISH 1	SCALE 5:1	SHEET 1 of 1
4 PLC ±			REV F1	
ANGLES ±				

1471-9 (1/15)

644540

A