



7. CABLE ACCOMMODATION DIMS:
 JACKET DIA. ----- .088 MAX.
 DIELECTRIC DIA. ----- .032-.042
 INNER CONDUCTOR DIA. --- .009-.019
 FOR USE WITH EXTRUDED OR WRAPPED JACKET.

6. FOR ELECTRICAL & MECHANICAL SPECS. SEE MALCO CATALOG.

5. .016 DIA. WIRE HOLE 3 PLACES

4. DELETED

3. GOLD PLATE PER MIL-G-45204 TYPE II, GR.C, CL. I
 2. SEE RF-ASMB-8 ASSY INSTRUCTIONS. SPECIAL TOOL REQ'D:
 CONTACT CRIMP: 010-0134-0000 & LOCATOR 001-0104-0000.
 ALTERNATE TOOL 010-0065-0000 (NO LOCATOR REQUIRED)
 HOUSING CRIMP: 010-0081-0000.

1. THIS CONNECTOR MATES WITH ALL 50Ω GOLDEN CRIMP, CRIMP SILVER & ALL S-50 JACKS & RECEPTACLES AS LISTED IN MICRODOT CATALOG.

NOTES: UNLESS OTHERWISE SPECIFIED

TYCO CUSTOMER
 DWG 7-1532149-6

4	3	2	1	COMPONENT No.	NOMENCLATURE	MAT'L & SPEC.	ITEM
					DELETED		11
				003-0815-0001	SEALING SLEEVE	SILICONE RUBBER MIL-R-5847	10
3				003-0813-0002	MIDDLE SLEEVE	LEADED COPPER	9
3				003-0814-0002	INNER SLEEVE	BRASS, QD-B-626	8
				003-0811-0001	CABLE INSULATOR	TEFLON PER L-P-403	7
				003-1301-0001	BODY INSULATOR	TEFLON PER L-P-403	6
3				003-0807-0002	PIN CONTACT	COPPER ALLOY	5
3	3			003-1299-0004	HOUSING SUB-ASSY NUT-1/4" HEX W/WIRE HOLES		4
3		1		003-1299-0003	HOUSING SUB-ASSY NUT-1/4" HEX		3
3			1	003-1299-0002	HOUSING SUB-ASSY NUT-1/4" KNURL		2
3			1	003-1299-0001	HOUSING SUB-ASSY NUT-1/4" PARTIAL HEX		1

ASSEMBLY NO. 132-0112-000	REV. J	DATE 7/22/65	APP. [Signature]	STANDARD TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONAL ANGLES OF ECCENTRICITY MAX. FIL. HOLE DIA. SURFACE ROUGHNESS MICRO INCHES THREADS TO MIL-S-772 COMMERCIAL TOLERANCES APPLY TO STOCK DIMENSIONS	MALCO A MICRODOT COMPANY, INC. 220 PASADENA AVE., SO. PASADENA, CALIF. SURFACE TREATMENT NOTED MATERIAL NOTED APP. R.B.C. APP. J.L. 7/1/65 CHECKED BY DRAWN BY U.M. SCALE 1:1 DATE 6/22/65 PROD. CODE 941 CODE CDM 132-0112-000* J DRAWING NUMBER
NEXT ASSY: [Blank]	REV. DESCRIPTION: UPDATED REV. LETTER	DATE: 7/22/65	APP. [Signature]	PLUG ASSEMBLY NON-ENVIRONMENTAL GOLDEN CRIMP 50Ω	