

915 Receptacle angled rotatable

9-pin Earth-to-Housing Connection according to VDE 0627 flange mount /Flange 25x25

E ED A 202 NN 00 00 0800 000 E G A 202 N 00 00 0800 000



Contact Arrangement mating view



Contacts (not part of product contents)

Tools (not part of product contents)


© 2018 TE Connectivity

TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Specifications and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mail: intercontec@te.com Web: www.intercontec.biz





Main Dimensions Receptacle angled rotatable

*for max. wire cross-section pay attention to the cross-section of used contacts

number of pins power signal temperature range protection type

Technical Data

Electrical Data rated current rated voltage rated insulation voltage (L-L)

mating cycles

pollution degree

Material

housing insulation insert seals

over voltage category max. height for operation 6000 V 500

3 III

FKM

2000 m

9

5

4 (3+PE)

power

max. 14 A*

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

zinc diecast / nickel plated PBT, PA, UL 94/V0

630V (AC/DC)

-20 °C to 130 °C when connected IP 66/67

> signal max. 3.6 A* 63 V (AC/DC)

1500 V