


CIRCUIT DIAGRAM



Dustproof:
 Protection class IP 54 acc. to IEC 529 (EN 60529)
 All plug-terminals
 Terminals shape similar to ISO 8092-1
 Coil and Load Terminals 6.3 mm±0.1 mm x 0.8 mm±0.05 mm

PART	MATERIAL	COLOUR
Cover	PA 66 GF 25	Black sim. to RAL 9005
Base	PA 66 GF 25	Black sim. to RAL 9005
Coil Terminals 85 and 86	CuSn	Sn plating
Load terminals 30, 87 and 87a	E-Cu	Sn plating

Nominal Voltage: 12 V
 Coil Resistance: 91 Ohm ±10% at 23° C

1) At Base level.

PART NUMBER	REV	TE PART NAME	COUNTRY OF ORIGIN
2-1393302-3	B	VF415F13/X811	Portugal

PROPRIETARY
 THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.

CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD

PAPER SIZE
A2

APPLICABLE SPEC.: FINISH
 DIMENSIONS APPLY PLATING
 SCALE 2:1 WEIGHT
 MATERIAL

REV.	CHANGE ORDER	DATE	APP.	DATE	NAME	PART NAME
A1	INITIAL DRAWING	24JAN2022	LSan	10NOV2021	L.Sandoval	POWER F RELAY CHANGE OVER 12V
A	---	18NOV2021	LSan			
LOCATION PE EVORA 						DWG NO. C - V23134-A0052-X811 CUSTOMER DRAWING
						SHT. 1 OF 1

