

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type ECV Wire Combinations  
Catalog No. 328890 and 330021  
Circular Mil Range 3,248 to 4,872 — Use “18-16 EC” Tooling  
Strip Length — 7.94 mm [.313 in.] Min  
8.73 mm [.344 in.] Max**



105°C [222°F] Max

**UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F] Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4-5	3-4	2	1
	2	3-4	2-3	1-2	1
	3	2-3	1-2	1	1
	4	1-2	1	1	—
	5	1	1	—	—
20	1	3-5	2-3	2	1
	2	2-3	1-2	1	1
	3	1-2	1	1	—
	4	1	—	—	—
18	1	2-4	2	1-2	1
	2	1-2	1	1	—
16	1	1-3	1-2	1	—

**INSTRUCTIONS:** Twist wires together before crimping. Minimum load is five wires size 22 AWG.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type ECV Wire Combinations  
Catalog No. 328890 and 330021  
Circular Mil Range 3,248 to 4,872 — Use “18-16 EC” Tooling  
Strip Length — 7.94 mm [.313 in.] Min  
8.73 mm [.344 in.] Max**



105°C [222°F] Max

**UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F] Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4-5	3-4	2	1
	2	3-4	2-3	1-2	1
	3	2-3	1-2	1	1
	4	1-2	1	1	—
	5	1	1	—	—
20	1	3-5	2-3	2	1
	2	2-3	1-2	1	1
	3	1-2	1	1	—
	4	1	—	—	—
18	1	2-4	2	1-2	1
	2	1-2	1	1	—
16	1	1-3	1-2	1	—

**INSTRUCTIONS:** Twist wires together before crimping. Minimum load is five wires size 22 AWG.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type ECV Wire Combinations  
Catalog No. 328890 and 330021  
Circular Mil Range 3,248 to 4,872 — Use “18-16 EC” Tooling  
Strip Length — 7.94 mm [.313 in.] Min  
8.73 mm [.344 in.] Max**



105°C [222°F] Max

**UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F] Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4-5	3-4	2	1
	2	3-4	2-3	1-2	1
	3	2-3	1-2	1	1
	4	1-2	1	1	—
	5	1	1	—	—
20	1	3-5	2-3	2	1
	2	2-3	1-2	1	1
	3	1-2	1	1	—
	4	1	—	—	—
18	1	2-4	2	1-2	1
	2	1-2	1	1	—
16	1	1-3	1-2	1	—

**INSTRUCTIONS:** Twist wires together before crimping. Minimum load is five wires size 22 AWG.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type ECV Wire Combinations  
Catalog No. 328890 and 330021  
Circular Mil Range 3,248 to 4,872 — Use “18-16 EC” Tooling  
Strip Length — 7.94 mm [.313 in.] Min  
8.73 mm [.344 in.] Max**



105°C [222°F] Max

**UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F] Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4-5	3-4	2	1
	2	3-4	2-3	1-2	1
	3	2-3	1-2	1	1
	4	1-2	1	1	—
	5	1	1	—	—
20	1	3-5	2-3	2	1
	2	2-3	1-2	1	1
	3	1-2	1	1	—
	4	1	—	—	—
18	1	2-4	2	1-2	1
	2	1-2	1	1	—
16	1	1-3	1-2	1	—

**INSTRUCTIONS:** Twist wires together before crimping. Minimum load is five wires size 22 AWG.