



PIDG* Pressure Type Wire Connectors, Terminals
(Use Tooling for PIDG Terminals or TETRA-CRIMP* Tooling)

408-2049-4
21 JUN 23 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



WIRE SIZE RANGE (AWG) AND TYPE	DESCRIPTION
22-16 STRANDED OR SOLID	300 V Max 105°C [222°F] Max (Vinyl and Nylon)
16-14 STRANDED OR SOLID	
12-10 STRANDED OR SOLID	

NOTE: Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies. All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at www.te.com

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.



PIDG* Pressure Type Wire Connectors, Terminals
(Use Tooling for PIDG Terminals or TETRA-CRIMP* Tooling)

408-2049-4
21 JUN 23 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



WIRE SIZE RANGE (AWG) AND TYPE	DESCRIPTION
22-16 STRANDED OR SOLID	300 V Max 105°C [222°F] Max (Vinyl and Nylon)
16-14 STRANDED OR SOLID	
12-10 STRANDED OR SOLID	

NOTE: Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies. All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at www.te.com

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.



PIDG* Pressure Type Wire Connectors, Terminals
(Use Tooling for PIDG Terminals or TETRA-CRIMP* Tooling)

408-2049-4
21 JUN 23 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



WIRE SIZE RANGE (AWG) AND TYPE	DESCRIPTION
22-16 STRANDED OR SOLID	300 V Max 105°C [222°F] Max (Vinyl and Nylon)
16-14 STRANDED OR SOLID	
12-10 STRANDED OR SOLID	

NOTE: Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies. All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at www.te.com

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.



PIDG* Pressure Type Wire Connectors, Terminals
(Use Tooling for PIDG Terminals or TETRA-CRIMP* Tooling)

408-2049-4
21 JUN 23 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



WIRE SIZE RANGE (AWG) AND TYPE	DESCRIPTION
22-16 STRANDED OR SOLID	300 V Max 105°C [222°F] Max (Vinyl and Nylon)
16-14 STRANDED OR SOLID	
12-10 STRANDED OR SOLID	

NOTE: Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies. All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at www.te.com

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.



PIDG* Pressure Type Wire Connectors, Terminals
(Use Tooling for PIDG Terminals or TETRA-CRIMP* Tooling)

408-2049-4
21 JUN 23 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



WIRE SIZE RANGE (AWG) AND TYPE	DESCRIPTION
22-16 STRANDED OR SOLID	300 V Max 105°C [222°F] Max (Vinyl and Nylon)
16-14 STRANDED OR SOLID	
12-10 STRANDED OR SOLID	

NOTE: Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies. All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at www.te.com

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.



PIDG* Pressure Type Wire Connectors, Terminals
(Use Tooling for PIDG Terminals or TETRA-CRIMP* Tooling)

408-2049-4
21 JUN 23 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



WIRE SIZE RANGE (AWG) AND TYPE	DESCRIPTION
22-16 STRANDED OR SOLID	300 V Max 105°C [222°F] Max (Vinyl and Nylon)
16-14 STRANDED OR SOLID	
12-10 STRANDED OR SOLID	

NOTE: Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies. All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at www.te.com

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.