



## Y(S)8066

### Directional Yagi Antennas 809-896 MHz

Laird Connectivity's Silver Series Yagi antennas represent great value while featuring the same great optimized design and plated brass connector found on premium gold series models. Each Yagi is factory tuned on a network analyzer for best power match and lowest VSWR, offering the best possible performance every time. All antennas ship complete with a mounting kit that includes stainless steel hardware.

#### FEATURES AND BENEFITS

- All 450 MHz and higher frequency models are delivered fully assembled
- All radial elements are secured to the boom with stainless steel hardware to prevent corrosion
- Every Yagi is tuned on a network analyzer for best power match and lowest VSWR
- All antennas ship complete with a mounting kit that includes stainless steel hardware

#### APPLICATIONS

- Point-to-point and multi-point/ omnidirectional outdoor antenna applications used by private organizations and government agencies around the globe
- Typical applications include transportation such as railroad switching, remote locations reporting examples that include oil fields, weather conditions and, meter data transmissions for utilities

#### ELECTRICAL SPECIFICATIONS



Model Name	Y(S)8066
Operating Frequency (MHz)	809-896
VSWR	< 2:1
Return Loss - max (dB)	-10
Gain (dBd)	9.0
Front-to-Back Ratio (dBd)	15
Max Power - Ambient 25°C (W)	300
Nominal Impedance (Ohms)	50
Polarization	Vertical
Pattern	Directional
Horizontal Plane 3 dB Beamwidth	89°
Vertical Plane 3 dB Beamwidth	65°
Tuning	Fixed
Transmitting/Receiving	Both

## MECHANICAL SPECIFICATIONS

Dimensions - L x H - cm (inches)	42.55 x 18.42 (16-3/4 x 7-1/4)
Boom Diameter - cm (inches)	2.22 (7/8)
Weight - kg (lbs.)	0.79 (1.75)
Cable Type	N/A
Connector	N-female
Color	Bright dipped aluminum
Lightning Protection	Lightning arrester - LABH350NN (sold separately)
Mounting Kit (included)	Yagi mounting kit for 7/8-inch boom

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature - °C (°F)	-50 to +85°C (-58 to +185°F)
Rated Wind Velocity - km/hr (mph)	241 (150)
Equivalent Flat Area - sq. km (sq. ft.)	1.42 (0.1516)



Vertical-to-Vertical Polarization Azimuthal Pattern (Y, Z, or E-plane)

Horizontal-to-Horizontal Polarization Azimuthal Pattern (Y, Z, or H-plane)

## te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original

## TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015